

Product Information



Monolec® Engine Oil (8600, 8630)

Offers Dependable, Heavy-Duty Performance in Diesel Engines

Monolec® Engine Oil provides excellent service for engines in mobile equipment and stationary generators. With its formulation of select base oils, shear-stable viscosity improver and Monolec®, LE's exclusive wear-reducing additive, Monolec Engine Oil offers increased fuel efficiency, dependable performance and wear protection. It is designed specifically for applications requiring the CJ-4 specification for those companies and individuals not wanting to switch to a CK-4 fluid.

Beneficial Qualities

Cost-Saving Service

- Reduces oil consumption
- Increases fuel efficiency
- Improves reliability and minimizes downtime

Wear Prevention & Protection

- Provides maximum wear prevention
- Extends engine life
- Keeps engine parts clean with heavy-duty detergents and dispersants

All-Weather Performance

- Ensures minimal drag during low-temperature startups
- Effectively lubricates at high temperatures

Emissions Reduction

- Works in conjunction with EGR engines to manage soot and other exhaust contaminants
- Low SAPS formula minimizes poisoning of SCR systems and particulate filtration traps



Proprietary Additives

LE's proprietary additives are used exclusively in LE lubricants. Monolec® Engine Oil contains Monolec.

Monolec® wear-reducing additive creates a single molecular lubricating film on metal surfaces, vastly increasing oil film strength without affecting clearances. An invaluable component in LE's engine oils, industrial oils and many of its other lubricants, Monolec allows opposing surfaces to slide by one another, greatly reducing friction, heat and wear.



Asset Reliability Solutions™

www.LElubricants.com • 800-537-7683



Monolec® Engine Oil

	<u>8600</u>	<u>8630</u>
Color	Amber	Amber
SAE Grade	15W-40	10W-30
Relative Density @ 60°F/60°F, ASTM D1298	0.8713	0.8674
Viscosity @ 100°C, cSt, ASTM D445	15.20	12.33
Viscosity @ 40°C, cSt, ASTM D445	114.70	85.94
Viscosity Index ASTM D2270	138	139
Viscosity-HTHS @ 150°C, cP, ASTM D4683	4.02	3.5
Viscosity-CCS @ -20°C, cP, ASTM D5293	4,930	-
Viscosity-CCS @ -25°C, cP, ASTM D5293	-	5,856
Viscosity-MRV TP-1 @ -25°C, cP, ASTM D4684	18,600	-
Viscosity-MRV TP-1 @ -30°C, cP, ASTM D4684	-	19,260
Flash Point °C (°F), (COC), ASTM D92	221 (430)	221 (430)
Pour Point °C (°F), ASTM D97	-31 (-24)	-36 (-33)
Ash—Sulfated %, ASTM D874	1.00	1.00
Acid Number mg KOH/g, ASTM D664	3.25	3.26
Base Number ASTM D2896	9.0	9.0

Performance Requirements Met or Exceeded

- API-SAE Service CJ-4
- ACEA E7 (8600 only)
- Caterpillar ECF-3, ECF-2
- Cummins CES 20081
- Daimler MB 228.31 (8600 only)
- Detroit Diesel DFS 93K218
- Mack EO-O Premium Plus, EO-N
- MAN M3575 (8600 only)
- MTU Category 2.1 (8600 only)
- Renault RLD-3
- Volvo VDS-4, VDS-3

Typical Applications

- Diesel engines (fleet)
 - On- and off-road mobile equipment, including over-the-road tractor trailers, pickup trucks, construction equipment, farming equipment and more
 - Specially formulated for low-emission and ultra low sulfur diesel (ULSD) engine and backwards compatible for use in older diesel engines
- Diesel engines (industrial)
 - Stationary generators

Recommendations

- Compatible for use with diesel particulate filters
- Not for use with silver alloy bearings such as EMD engines (Electro-Motive Division of GM)