

Product Information



Xport™ Single Point Lubricators



Xport Classic Lubricator

Lubricant Volume

120 cc (4.06 fl oz)

Housing Design

Metal

Lubricant Discharge Period

1,3,6 or 12 months (Activator)

Operating Temperature Range

0 to 40°C (32 to 104°F)

Pressure Build-up

4 bar / 58 psi

Xport Futura Lubricator

Lubricant Volume

120 cc (4.06 fl oz)

Housing Design

Transparent Plastic

Lubricant Discharge Period

1,3,6 or 12 months (Activator)

Operating Temperature Range

0 to 40°C (32 to 104°F)

Pressure Build-up

4 bar / 58 psi

Xport Flex Lubricator

Lubricant Volume

60 or 125 cc (2.03 or 4.23 fl oz)

Housing Design

Transparent Plastic

Lubricant Discharge Period

1,2,3, ..., 12 months (Dial)

Operating Temperature Range

-20 to 60°C (-4 to 140°F)

Pressure Build-up

5 bar / 72.5 psi

Xport Nova Lubricator

Lubricant Volume

125 cc (4.23 fl oz)

Housing Design

Transparent Plastic

Lubricant Discharge Period

1,2,3, ..., 12 months (Push button)

Operating Temperature Range

-20 to 60°C (-4 to 140°F)

Pressure Build-up

6 bar / 87 psi



Xport Star Vario / Star Control Lubricator

Lubricant Volume

60, 125 or 250 cc (2.03, 4.23 or 8.45 oz)

Lubricant Discharge Period

Star Vario - 1, 2, 3, ..., 12 months (Push button)

Star Control - Time or Impulse controlled

Operating Temperature Range

-10 to 60°C (14 to 140°F)





Pressure Build-up

max. 6 bar / 87 psi



Xport™ Single Point Lubricators

Application Suitability

		Conveyors	Electric Motors	Pumps	Blowers/Fans
	Classic & Futura	++	O	+	+
	Flex	+	+	++	++
	Nova	+	++	+	++
	Star Vario & Star Control	++	++	++	++

O Limited suitability

+ Suitable

++ Very suitable



LEX-SPLLCFLY_132 5-16, rev. 9-18