

Product Information



Earthwise™ EAL Wire Rope Grease (3353)

Soft, Semifluid Coating Lubricant Lets You Go Green Without Sacrificing Performance

LE's Earthwise™ lubricants are specifically formulated to be earth friendly while still meeting the rigorous demands of industrial applications. With these products, you can "go green" – and keep up with the latest environmental regulations – without having to sacrifice performance.

Earthwise EAL Wire Rope Grease (3353) is a certified Environmentally Acceptable Lubricant (EAL), recommended for use in applications on or near waterways. It meets the specifications required by the EPA's Vessel General Permit (VGP). It is readily biodegradable, exhibits minimal aquatic toxicity and will not accumulate in the cells of fish and other aquatic life forms.

It is a soft, semifluid formulation designed to coat wire rope as well as moving chain and cable parts to ensure long life and smooth, quiet operation. Its semi-tacky, water-resistant characteristics enable it to adhere to the application and seal out damaging moisture and protect against rust formation. Its robust additive package, including LE's proprietary Almasol® and Quinplex® additives, further helps it protect against wear, corrosion, impact, rust and oxidation.

Beneficial Qualities

VGP Compliant

- Well-suited for applications in or around waterways
- Formulated with 100% biodegradable base fluid
- Meets VGP standard for aquatic toxicity
- Meets VGP standard for bioaccumulation
- Helps companies be good environmental stewards

Semi-Tacky & Water-Resistant

- Clings to metal surfaces, including moving parts
- Stays in place in presence of moisture for long service life

Wear-Reducing

- Reduces wear to wire rope and all moving parts, including chains & cables
- Protects sprockets, sheaves & other wear-intensive areas
- Seals surfaces, protecting against rust and corrosion
- Shields against acid attack

Smooth-Operating

- Softens shocks
- Enables metal joints and strands to move freely

Available Grade

- NLGI 0



Proprietary Additives

LE's proprietary additives are used exclusively in LE lubricants. Earthwise EAL Wire Rope Grease contains Almasol and Quinplex.

Almasol® solid wear-reducing additive is able to withstand extremely heavy loads, chemical attack and temperatures up to 1,900°F (1,038°C). It is attracted to metal surfaces, forming a microscopic layer but not building on itself or affecting clearances. Almasol minimizes metal-to-metal contact and the resulting friction, heat and wear.

Quinplex® contributes to outstanding water resistance, tackiness and enhanced mechanical stability, and helps to form a barrier against corrosion.





Earthwise™ EAL Wire Rope Grease

3353

Thickener Type	Aluminum Complex
Texture	Smooth
Color	Brown
NLGI Grade	0
Worked 60 Penetration ASTM D217	357
Dropping Point °C (°F), ASTM D2265	232 (450)
Base Fluid Characteristics	
Viscosity @ 100°C, cSt, ASTM D445	20.4
Viscosity @ 40°C, cSt, ASTM D445	128.5
Corrosion Prevention DI H2O, ASTM D1743	Pass
Readily Biodegradable Content %, OECD 301B	>75
Aquatic Toxicity mg/L, OECD 201/202/203	>1,000
Bioaccumulating Content %, OECD 305	0

Performance Requirements Met or Exceeded

- US EPA 2013 VGP
- USDA H2

Typical Applications

- Applications on or near waterways, including:
 - Wire rope
 - Chains (links, pins, bushings)
 - Cables (sheave bushings, bearings & strands)
 - Open and closed silent and roller chains
- Ideal for use in automatic wire rope lubricators

Recommendations

- Operating range: -29° to 200°C (-20 to 392°F)
- Not for high temps or when gear oil is specified



Approved for Use with Viper Wire Rope Lubricator

Documented use of Earthwise EAL Wire Rope Grease (3353) will double the warranty period of the Viper Wire Rope Lubricator to 24 months.