



# TECHNICAL DATA BULLETIN

## 4201-4204 White Utility Oil

### DESCRIPTION

Food and USP grade white mineral oil containing no additives. Meets the requirements of NSF H1 registered lubricants. Certified Halal by IFANCA. Certified Kosher Pareve.

### TECHNICAL DATA

	<u>4201</u>	<u>4204</u>
Color	Water White	Water White
SAE Grade / ISO VG	–	10 / 46
Relative Density @ 60°F/60°F, ASTM D1298	0.8800	0.889
Viscosity @ 100°C, cSt, ASTM D445	3.600	5.700
Viscosity @ 40°C, cSt, ASTM D445	18.00	43.00
Flash Point °C (F), (COC), ASTM D92	160 (320)	191 (375)
Pour Point °C (°F), ASTM D97	-40 (-40)	-37 (-35)

### APPLICATION

General lubrication applications where incidental food contact can occur. Suggested for rust prevention after washdown. Can also be used for textile applications where nonstaining oil is required. These include spindle oil and needle oil.

Caution: Do not use where R&O, AW or EP oils are required.

LEADERS IN LUBRICANTS

L150079 1-98, rev. 2-15

**LUBRICATION ENGINEERS, Inc.**

1919 E. Tulsa • Wichita, KS 67216  
817-916-3200 • 800-537-7683 • fax 817-820-1512  
www.LElubricants.com

**LE OPERATES UNDER AN ISO 9001  
CERTIFIED QUALITY SYSTEM.**